

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.10.2020

Version number 6

Revision: 26.10.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking


- 1.1 Product identifier
- Trade name: **KEMPEROL Fallstop**
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Application of the substance / the mixture: Coating
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: KEMPER SYSTEM GmbH & Co. KG
Holländische Strasse 32-36
34246 Vellmar
Deutschland / Germany
Telefon: +49 (0)561 / 8295-0
Telefax: +49 (0)561 / 8295-5110
E-Mail: MSDS@KEMPER-SYSTEM.COM
- Further information obtainable from: Research and Development
- 1.4 Emergency telephone number: Giftinformationszentrum der Länder Rheinland-Pfalz und Hessen
Langenbeckstraße 1; Gebäude 601; 55131 Mainz
Tel. Nr.: +49 (0)6131 / 19 24 0
Universitätsmedizin der Johannes Gutenberg-Universität Mainz


SECTION 2: Hazards identification


- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3	H226	Flammable liquid and vapour.
Acute Tox. 4	H332	Harmful if inhaled.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms


GHS02


GHS07


GHS09

The product is classified and labelled according to the CLP regulation.

- Signal word: Warning
- Hazard-determining components of labelling:

xylene
Urethane bis Oxazolidine
Isophorondiisocyanate homopolymer
ethylbenzene
hexahydromethylphthalic anhydride
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate
benzotriazole derivatives
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

- Hazard statements

H226 Flammable liquid and vapour.
H332 Harmful if inhaled.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

- Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- Additional information: EUH204 Contains isocyanates. May produce an allergic reaction.
- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.10.2020

Version number 6

Revision: 26.10.2020

Trade name: **KEMPEROL Fallstop**

- vPvB:

Not applicable.

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

- 3.2 Chemical characterisation: Mixtures

- **Description:** Mixture: consisting of the following components.

- Dangerous components:

CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	12.5-25%
CAS: 59719-67-4 EINECS: 261-879-6 Reg.nr.: 01-2119983487-19	Urethane bis Oxazolidine Aquatic Chronic 2, H411; Eye Irrit. 2, H319; Skin Sens. 1, H317	10-12.5%
CAS: 53880-05-0 EC number: 931-312-3 Reg.nr.: 01-2119488734-24	Isophorondiisocyanate homopolymer Skin Sens. 1, H317; STOT SE 3, H335	10-12.5%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-10%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	hydrocarbons, C9, aromatic Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	2.5-10%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Aquatic Chronic 3, H412	0.5-2.5%
CAS: 25550-51-0 EINECS: 247-094-1 Index number: 607-241-00-6 Reg.nr.: 01-2119845474-33	hexahydromethylphthalic anhydride Resp. Sens. 1, H334; Eye Dam. 1, H318; Skin Sens. 1, H317	<0.5%
CAS: 4098-71-9 EINECS: 223-861-6 Index number: 615-008-00-5 Reg.nr.: 01-2119490408-31	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate Acute Tox. 1, H330; Resp. Sens. 1, H334; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	<0.5%
ELINCS: 400-830-7 Index number: 607-176-00-3 Reg.nr.: 01-0000015075-76	benzotriazole derivatives Aquatic Chronic 2, H411; Skin Sens. 1, H317	<0.5%
EC number: 915-687-0 Reg.nr.: 01-2119491304-40	Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	<0.5%

- SVHC

25550-51-0 | hexahydromethylphthalic anhydride

- Additional information:

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures

- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Do not leave affected persons unattended.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

- After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment in case of complaints.

- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Protect unharmed eye.

- After swallowing:

If symptoms persist consult doctor.

- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.10.2020

Version number 6

Revision: 26.10.2020

Trade name: **KEMPEROL Fallstop**

(Contd. of page 2)

- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire extinguishing methods suitable to surrounding conditions.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture: Formation of toxic gases is possible during heating or in case of fire.
- 5.3 Advice for firefighters: Do not inhale explosion gases or combustion gases.
- Protective equipment:
- Additional information: Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away. Avoid contact with skin and eyes. Ensure adequate ventilation
- 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Prevent from spreading (e.g. by damming-in or oil barriers). Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Do not flush with water or aqueous cleansing agents
- 6.4 Reference to other sections: See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling: Store in cool, dry place in tightly closed receptacles. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage: Store only in the original receptacle.
- Requirements to be met by storerooms and receptacles: Store away from foodstuffs.
- Information about storage in one common storage facility:
- Further information about storage conditions: Recommended storage temperature: 5-30 °C. Store in dry conditions. Protect from frost. Keep container tightly sealed.
- Storage class: 3
- 7.3 Specific end use(s): No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.10.2020

Version number 6

Revision: 26.10.2020

Trade name: **KEMPEROL Fallstop**

(Contd. of page 3)

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm
Long-term value: 441 mg/m³, 100 ppm
Sk

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

WEL Short-term value: 0.07 mg/m³
Long-term value: 0.02 mg/m³
Sen; as -NCO

- Regulatory information

WEL: EH40/2020

- DNELs

1330-20-7 xylene

Inhalative	Acute - systemic effects	221 mg/m ³ (Worker) (GESTIS DNEL List (June 2018))
	Long term - systemic effects	221 mg/m ³ (Worker) (GESTIS DNEL List (June 2018))

100-41-4 ethylbenzene

Inhalative	Long term - systemic effects	77 mg/m ³ (Worker) (GESTIS DNEL List (June 2018))
------------	------------------------------	--

- Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

BMGV 1 µmol creatinine/mol
Medium: urine
Sampling time: At the end of the period of exposure
Parameter: isocyanate-derived diamine

- Additional information:

The lists valid during the making were used as basis.

- 8.2 Exposure controls

- Personal protective equipment:

- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

- Respiratory protection:

When used properly and under normal conditions, breathing protection is not required.
Use suitable respiratory protective device in case of insufficient ventilation.
Filter A/P2
Respiratory protection - Gas filters and combination filters according to (DIN EN 141)

- Protection of hands:



Protective gloves

Check protective gloves prior to each use for their proper condition.
Only use chemical-protective gloves with CE-labelling of category III.
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.

- Material of gloves

Recommended materials:
Butyl rubber, BR
Recommended thickness of the material: ≥ 0.5 mm
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.10.2020

Version number 6

Revision: 26.10.2020

Trade name: **KEMPEROL Fallstop**

(Contd. of page 4)

- As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR
Recommended thickness of the material: ≥ 0.1 mm
Penetration time (min.): < 10

- Eye protection:



Tightly sealed goggles

Protective goggles and facial protection - Classification according to EN 166 protective clothing (EN 13034)

- Body protection:

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Appearance:

Form: Fluid
Colour: According to product specification
Odour: Characteristic
Odour threshold: Not determined.

- pH-value: Not determined.

- Change in condition

Melting point/freezing point: Undetermined.
Initial boiling point and boiling range: 137 °C

- Flash point: 41 °C (DIN EN ISO 1523)

- Flammability (solid, gas): Not applicable.

- Decomposition temperature: Not determined.

- Auto-ignition temperature: Product is not selfigniting.

- Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- Explosion limits:

Lower: Not determined.
Upper: Not determined.

- Density at 20 °C: 1.01 g/cm³

- Relative density: Not determined.

- Vapour density: Not determined.

- Evaporation rate: Not determined.

- Solubility in / Miscibility with water: Not miscible or difficult to mix.

- Partition coefficient: n-octanol/water: Not determined.

- Viscosity:

Dynamic: Not determined.
Kinematic at 20 °C: 107 s (ISO 6 mm)

- Solvent content:

VOC (EC) < 26.80 %

- 9.2 Other information: No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity: No further relevant information available.

- 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions

No dangerous reactions known.

- 10.4 Conditions to avoid

No further relevant information available.

- 10.5 Incompatible materials:

No further relevant information available.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.10.2020

Version number 6

Revision: 26.10.2020

Trade name: **KEMPEROL Fallstop**

- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

(Contd. of page 5)

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects

- **Acute toxicity** Harmful if inhaled.

- LD/LC50 values relevant for classification:

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)

59719-67-4 Urethane bis Oxazolidine

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rab)

53880-05-0 Isophorondiisocyanate homopolymer

Oral	LD50	>14,000 mg/kg (rat) (OECD 401)
------	------	--------------------------------

1330-20-7 xylene

Oral	LD50	5,251 mg/kg (mouse) 4,300 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	21.7 mg/l (rat)

hydrocarbons, C9, aromatic

Oral	LD50	>3,492 mg/kg (rat) (OECD 401)
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)

100-41-4 ethylbenzene

Oral	LD50	3,500 mg/kg (rat) (AMA Archives of Industrial Health. 14/387; 1956)
Dermal	LD50	15,400 mg/kg (rabbit) (Food and Cosmetics Toxicology. 13/803; 1975)
Inhalative	LC50/4 h	11 mg/l (ATE)

25550-51-0 hexahydromethylphthalic anhydride

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Inhalative	LC50/4 h	0.05 mg/l (ATE)
------------	----------	-----------------

benzotriazole derivatives

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Oral	LD50	>2,300 mg/kg (rat) (IUCLID)
Inhalative	NOAEC	6.3 mg/l (daphnia) ((21 day))

- Primary irritant effect:

- **Skin corrosion/irritation**

Based on available data, the classification criteria are not met.

- **Serious eye damage/irritation**

Causes serious eye irritation.

- **Respiratory or skin sensitisation**

May cause an allergic skin reaction.

- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

- **Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

- **Carcinogenicity**

Based on available data, the classification criteria are not met.

- **Reproductive toxicity**

Based on available data, the classification criteria are not met.

- **STOT-single exposure**

Based on available data, the classification criteria are not met.

- **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

- **Aspiration hazard**

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- 12.1 Toxicity

- Aquatic toxicity:

64742-95-6 Solvent naphtha (petroleum), light arom.

LL 50	9.2 mg/l (fish) (96h; OECD 203)
EC50	3.2 mg/l (Daphnia magna) (48h; OECD 202)
EC50	2.6 mg/l (Pseudokirchneriella subcapitata) (72h; OECD 201)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.10.2020

Version number 6

Revision: 26.10.2020

Trade name: **KEMPEROL Fallstop**

(Contd. of page 6)

59719-67-4 Urethane bis Oxazolidine

EC50	87.1 mg/l (Daphnia magna) (48h)
EC50	18.6 mg/l (Selenastrum capricornutum) (72h)

53880-05-0 Isophorondiisocyanate homopolymer

LC50/96 h	>1.51 mg/l (Cyprinus Carpio) (Richtlinie 67/548/EWG, Anhang V, C.1.)
EC50	>3.36 mg/l (Daphnia magna) (OECD 202)
EC50	>10,000 mg/l (Belebtschlamm) (OECD 209)

1330-20-7 xylene

LC50/96 h	26.7 mg/l (Pimephales promelas)
LC50	2.6 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (96h; OECD 203)
EC50	2.2 mg/l (Pseudokirchneriella subcapitata) (72h; OECD 201)
IC50	2.2 mg/l (ALGAE)
NOEC	157 mg/l (Belebtschlamm) (OECD 209)
	1.17 mg/l (Ceriodaphnia dubia) (7d; US EPA 600/4-91/003)
	>1.3 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (56d)
IC50	1 mg/l (Daphnia magna) (24h; OECD 202)

hydrocarbons, C9, aromatic

LL 50	9.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (96h; OECD 203)
EL50	2.9 mg/l (Pseudokirchneriella subcapitata) (72h; OECD 201)
	3.2 mg/l (Daphnia magna) (48h; OECD 202)
EC50	>99 mg/l (Belebtschlamm) (10 min.; OECD 209)

benzotriazole derivatives

NOEC	100 mg/kg (Eisenia fetida/foetida) (56d; OECD 222)
LC50/96 h	2.8 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (OECD 203; ISO 7346; 84/449/EWG, C1 stat.)
EC50	>1,000 mg/l (Belebtschlamm) (3h; OECD 209)
EC50	4 mg/l (Daphnia magna) (48h;)
EC10	10 mg/l (Pseudokirchneriella subcapitata) (72h; OECD 201)
EC50	>100 mg/l (Pseudokirchneriella subcapitata) (72h; OECD 201)
NOEC	0.78 mg/l (Daphnia magna) (21d; OECD 202, Part 2)

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

LC50/96 h (static)	0.97 mg/l (LEPOMUS MACROCHIRUS) (OECD 203; IUCLID)
EC50	0.22 mg/l (ALGAE) ((72 hr))
EC50	20 mg/l (Daphnia magna) (OECD 202/1; IUCLID)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:** Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal according to official regulations

- European waste catalogue

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
08 04 10	waste adhesives and sealants other than those mentioned in 08 04 09

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.10.2020

Version number 6

Revision: 26.10.2020

Trade name: **KEMPEROL Fallstop**

(Contd. of page 7)

- Uncleaned packaging:

- Recommendation:

Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1 UN-Number
- ADR, IMDG, IATA

UN1263

- 14.2 UN proper shipping name

- ADR
- IMDG

1263 PAINT, ENVIRONMENTALLY HAZARDOUS
PAINT (Solvent naphtha (petroleum), light arom., Urethane bis Oxazolidine),
MARINE POLLUTANT
PAINT

- IATA

- 14.3 Transport hazard class(es)

- ADR



- Class 3 (F1) Flammable liquids.
- Label 3

- IMDG



- Class 3 Flammable liquids.
- Label 3

- IATA



- Class 3 Flammable liquids.
- Label 3

- 14.4 Packing group
- ADR, IMDG, IATA

III

- 14.5 Environmental hazards:

Product contains environmentally hazardous substances: bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

- Marine pollutant:

Yes

- Special marking (ADR):

Symbol (fish and tree)
Symbol (fish and tree)

- 14.6 Special precautions for user

Warning: Flammable liquids.

- Hazard identification number (Kemler code):

30

- EMS Number:

F-E,S-E

- Stowage Category

A

- 14.7 Transport in bulk according to Annex II of Marpol and the IBC
Code

Not applicable.

- Transport/Additional information:

- ADR

- Limited quantities (LQ)

5L

- Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

- Transport category

3

- Tunnel restriction code

D/E

(Contd. on page 9)

EN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.10.2020

Version number 6

Revision: 26.10.2020

Trade name: **KEMPEROL Fallstop**

(Contd. of page 8)

- IMDG	
- Limited quantities (LQ)	5L
- Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
- UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** E2 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 74

- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

- **National regulations:**

- **Information about limitation of use:** Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.
Employment restrictions concerning women of child-bearing age must be observed.

- **Other regulations, limitations and prohibitive regulations**

- **Substances of very high concern (SVHC) according to REACH, Article 57**

25550-51-0 | hexahydromethylphthalic anhydride

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

- **Department issuing SDS:**

research & development

- **Contact:**

research & development

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.10.2020

Version number 6

Revision: 26.10.2020

Trade name: KEMPEROL Fallstop

(Contd. of page 9)

LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity - dermal – Category 4
Acute Tox. 1: Acute toxicity - inhalation – Category 1
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- **Sources**

- www.echa.europa.eu
- www.baua.de
IFA: Institute für Occupational Safety and Health of the German Social Accident Insurance:
- www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp
- www.dguv.de/ifa/gestis/gestis-dnel-liste

- * **Data compared to the previous version altered.**