

KEMPEROL TP talcum

Uses

To reduce dirt retention

Pack sizes

25 kg bag

Shelf Life

Unlimited when stored in dry conditions.

Usage guide

At least 0,1 kg/m².

Properties

Form	Powder

^{*} Values obtained at a temperature of 23 °C - 50% rel. humidity. These values vary depending on the weather conditions, such as wind, humidity and temperature.

CE marking

Component to 2 ETA 03/0025 ETA 03/0026

Application

KEMPEROL TP Talcum at the earliest after 12 hours, on KEMPEROL V 210 waterproofing should be spread, distributed with a fine broom and swept together. KEMPEROL TP Talcum can be used again in a limited extent.

Important notes

KEMPEROL TP talcum is not subject to specific labelling according to the Ordinance on Hazardous Substances (GefStoffV).

General information

No substances of other systems may be mixed into the products of the KEMPER SYSTEM.

Only for commercial use.

Our technical data sheets / technical information and application instructions reflect the current level of knowledge in our company and the experience with our products. In each case, the new edition supersedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current code of practise. The latest version can be retrieved from the KEMPER SYSTEM Login section. When using our products, a detailed, object-related and qualified inspection is required in each individual

case in order to determine whether the product and /or application technology in question meets the specific requirements and purposes. We are liable only for our products being free from faults, and this only if our relevant product has been used and applied according to the instructions in our technical data sheets. Correct application of our products therefore falls entirely within the scope of liability and responsibility of the user (contractor). Our products are sold exclusively on the bases of our conditions of sale and delivery.

Issued: Vellmar, 2021-03-15